

➔ BUSINESS SHREDDER IDEAL 4005

INNOVATIVE HIGH CAPACITY OFFICE SHREDDERS – HIGH PERFORMANCE AND LARGE VOLUME

“SPS”- (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; “EASY_SWITCH” – intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off in case of a paper jam; automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy-saving mode after 1 hour | photo cell controlled automatic start and stop | “ECC” - Electronic Capacity Control – indication of the used sheet capacity during shredding process | automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance | convenient 405 mm feed opening | high quality paper clip proof² cutting shafts from special hardened steel | models IDEAL 4005 and IDEAL 4005-C/C suitable for safe shredding of CDs | 5 years guarantee² on the cutting shafts | quiet but powerful 1600 Watt single phase motor for continuous operation | dust-proof gear box housing | high-quality wooden cabinet, mobile on castors | plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag (models M/C and SM/C with shred container) | approx. 225 litres volume for the shreds

Power connection³: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 1010 x 640 x 590 mm, Weight: 115 kg



“ECC” CONTROL



..ECC” – Electronic Capacity Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

➔ IDEAL 4005

Shred width	6 mm
Sheet capacity ¹	50-55 42-47
Security level	2
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-C/C

Particle size	4 x 40 mm
Sheet capacity ¹	40-45 34-39
Security level	3
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-C/C

Particle size	2 x 15 mm
Sheet capacity ¹	25-30 21-26
Security level	4
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-M/C

Particle size	0.8 x 12 mm
Sheet capacity ¹	15-17 13-15
Security level	5
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-SM/C

Particle size	0.8 x 5 mm
Sheet capacity ¹	10-11 8-9
Security level	“Level 6”
Feed opening	405 mm
Motor capacity	1600 Watt

¹ A4 paper, 70 g/m² | 80 g/m²
² 4005-M/C 0.8 x 12 mm and 4005-SM/C 0.8 x 5 mm: Paper clips and staples have to be removed before shredding. Guarantee 1 year.
³ other voltages available



L.T.E. Listed 802 D